



Product data sheet **KP52F**

| | |
|------------------|---|
| Backing | F-paper |
| Bonding | Synthetic resin |
| Grain | Aluminium oxide |
| Coating | Half open |
| Application area | Resinous wood, solid wood and softwood |
| Application | Wide-belt and long-belt grinding machines, edge-belt grinding machines |
| Advantages | <p>A rapid clogging with grinding dust is prevented by the half-open dispersion and anti-static coating. This quality is particularly good for wood working.</p> <p>Available as a jumbo roll in 2 widths: 1425 mm and 1865 mm (Off-cut optimisation)</p> |



Available grits

| | | | | | | | | | | | | | | | | | | | | | | | | | |
|----|----|----|----|----|----|----|----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|------|------|
| 16 | 20 | 24 | 30 | 36 | 40 | 50 | 60 | 80 | 100 | 120 | 150 | 180 | 220 | 240 | 280 | 320 | 360 | 400 | 500 | 600 | 800 | 900 | 1000 | 1200 | 1500 |
|----|----|----|----|----|----|----|----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|------|------|

Application



Manual sanding Stationary machine sanding

Product range



Rolls Wide belts Narrow belts Segment belts

AWUKO ABRASIVES
 Wandmacher GmbH & Co. KG
 Hedemündener Straße 9
 34346 Hann. Münden

info@awuko.com
 www.awuko.com